MOL-LUB Ltd.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: MOL Aluroll 2EPG metallurgical lubricating grease

Version: 2 Latest revision: 20. 03. 2012 Date of issue: 20. 06. 2007 Page: 1/(11)

1. Identification of the mixture and of the company/undertaking

1.1 Product identifier:

MOL Aluroll 2EPG metallurgical lubricating grease

1.2 Relevant identified uses of the mixture and uses advised against

Relevant identified uses: metallurgical lubricating grease

Uses advised against: no data

1.3 Details of the supplier of the safety data sheet:

MOL-LUB Lubricant Production Trade and Service Limited Liability Company

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 34 526 330 / +36 34 526 391

Request SDS of:

MOL-LUB Lubricant Production Trade and Service Limited Liability Company

Customer Service Center

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 80 201 296 / +36 34 348 010

Responsible for SDS:

MOL-LUB Ltd. Csaba Horváth, head of HSE, SD and QOP

Phone: +36 34 526 343; Mobile: +36 20 474 2644

e-mail: csahorvath@mol.hu

Technical information:

MOL-LUB Ltd. Product Development and Technical Service

H-1117 Budapest, Október huszonharmadika utca 18., Hungary

Phone/Fax: +36 80 201 296 or +36 1 464 0236 / +36 1 464 0304

1.4 Emergency telephone number

Emergency telephone (on workdays: 07-15²⁰ h (CET)): +36 34 526 210

Health Toxicological Information Service (ETTSZ 1096 Budapest, Nagyvárad tér 2.)

Tel.: +36 1 476 6464, or +36 80 201 199

National Health Toxicological Information Service:

MOL-LUB Ltd.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: MOL Aluroll 2EPG metallurgical lubricating grease

Version: 2 Latest revision: 20. 03. 2012 Date of issue: 20. 06. 2007 Page: 2/(11)

2. Hazards identification

2.1 Classification of the mixture

2.1.1 Classification of the mixture according to regulation (EC) No 1272/2008

Hazard Class and Category: Hazard statement:

.

2.1.2 Classification of the mixture according to regulation (EC) No 1999/45

Human health hazards: Danger symbol not required.

Note: Prolonged and/or repeated contact may cause irritation on

skin or in eyes depending on individual sensitivity (See

also Protective equipment).

Safety hazards: Danger symbol not required.

Environmental hazards: Danger symbol not required.

Note: Large spillages may be hazardous to the environment.

2.2 Label elements (EC) No 1272/2008

Product identification:

Trade name: MOL Aluroll 2EPG metallurgical lubricating grease

Pictogram: not required Signal word: not required

Hazard statement:

-

Precautionary statements – Prevention:

P273 Avoid release to the environment.

Precautionary statements – Disposal:

P501 Dispose of contents/container in accordance with national regulation.

MOL-LUB Ltd.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: MOL Aluroll 2EPG metallurgical lubricating grease

Version: 2 Latest revision: 20. 03. 2012 Date of issue: 20. 06. 2007 Page: 3/(11)

Other liabilities for labelling:

Tactile warning of danger: Not required. Transport classification: see section 14.

2.3 Other hazards

no data available

3. Composition/information on ingredients

3.1 Mixtures

Chemical description: Mineral oil based consistent lubricant containing complex

aluminium soap, additives and graphite.

Component / Hazardous component(s):

Name	EINECS number	CAS number	Hazard symbol / Hazard classes and cat.	Risk phrase / Hazard statements	Conc. %(m/m)
Lubricating oils	309-877-7	101316-72-7	67/548/EEC:)	
(petroleum), C24-			-	-	
C50*			(Note L)		
Registration Nr.:			1272/2008/EC:		
01-2119489969-06			Asp.Tox.1	H304	
			(Note L)		0.5
Lubricating oils	309-874-0	101316-69-2	67/548/EEC:		max. 95
(petroleum), C>25*			-	-	
Registration Nr.:			(Note L)		
01-2119486987-11			1272/2008/EC:		
			-	-	
			(Note L)	<i>J</i>	
4,4'-methylene bis	233-593-1	10254-57-6	67/548/EEC		max. 1.5
(dibutyldithiocarbamate)			Xi	R 36/38	
×			1272/2008/EC:		
REACH Registr. Nr.			Skin Irrit. 2	H315	
01-2119708416-41			Eye Irrit. 2	H319	
Long-chain alkenyl		confidential	67/548/EEC		max. 0.3
amine			C, Xn, N	R 35, R 22,	
₹				R 50	
			1272/2008/EC:		
			Skin Corr. 1A	H314	
			Acute Tox. 4	H302	
			Aquatic Acute 1	H400	

MOL-LUB Ltd.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: MOL Aluroll 2EPG metallurgical lubricating grease

Version: 2 Latest revision: 20. 03. 2012 Date of issue: 20. 06. 2007 Page: 4/(11)

	EINECS	CAS	Hazard symbol /	Risk phrase /	Conc.
Name	number	number	Hazard classes and	Hazard	%(m/m)
	number	number	cat.	statements	/0(111/111)
Zinc alkyl dithiophosphate	272-028-3	68649-42-3	67/548/EEC		max. 0.25
× *			Xi, N	R 41, R 38,	
				R 51/53	
			1272/2008/EC:		
			Eye Dam. 1	H318	
			Skin Irrit. 2	H315	
			Aquatic Chronic 2	H411	
Alkyl phosphonate		confidential	67/548/EEC		max. 0.15
× *			Xi, N	R 38, R 41,	
				R 51/53	
			1272/2008/EC:		
			Skin Irrit. 2	H315	
			Eye Dam. 1	H318	
			Aquatic Chronic 2	H411	

^{*:} with exposure limit

The full text of each relevant R-, H- phrase and Hazard classes and cat. see in Section 16.

4. First aid measures

4.1 Description of first aid measures

General information: Never give anything by mouth to an unconscious person, or never

induce vomiting.

Inhalation: Remove the affected person to fresh air. Seek medical attention.

Skin Remove contaminated clothing. Wash with plenty amount of water, using

contact: soap. In case of persistent irritation, get medical advice.

Eye contact: Flush eyes with large amounts of water for at least 15 minutes. Get medical

attention.

Ingestion: If swallowed, give drink salted lukewarm water. Induce vomiting. Get

medical attention

4.2 Most important symptoms and effects, both acute and delayed

-

4.3 Indication of any immediate medical attention and special treatment need Not required.

MOL-LUB Ltd.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: MOL Aluroll 2EPG metallurgical lubricating grease

Version: 2 Latest revision: 20. 03. 2012 Date of issue: 20. 06. 2007 Page: 5/(11)

5. Fire-fighting measures

Fire hazards:

See also Section 9 - flash point.

5.1 Extinguishing media

Suitable extinguishing media:

Sand, carbon dioxide, dry chemical powder.

Unsuitable extinguishing media:

Water jet.

5.2 Special hazards arising from the mixture

Hazardous combustion products:

On burning, carbon monoxide, carbon dioxide, sulphur oxides, nitrogen oxides, phosphor oxides, various hydrocarbons and soot can be formed.

5.3 Advice for fire-fighters

Special protective equipment:

According to the existing fire-fighting regulations.

Further information:

-

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: see Section 8.

Danger of slipping on leaked out/spilled product.

6.2 Environmental precautions:

Confine spills to prevent material from entering sewers, watercourses, drains and into soil Notify relevant authority.

6.3 Methods and material for containment and cleaning up

On soil: Take up spilled product with shovel or scoop. Residuals should be cleaned

up with cloths and/or sawdust. Dispose of the collected material as

hazardous waste, according to local regulations.

On water: Confine the spillage. Remove from surface by skimming. Notify local

authorities according to regulations.

6.4 Reference to other sections

Personal precautions: see section 8.

Waste treatment methods: see section 13.

MOL-LUB Ltd.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: MOL Aluroll 2EPG metallurgical lubricating grease

Version: 2 Latest revision: 20. 03. 2012 Date of issue: 20. 06. 2007 Page: 6/(11)

7. Handling and storage

7.1 Precautions for safe handling

General measures for handling lubricant greases should be observed.

Avoid splashing the product.

Avoid contact with skin and eyes.

Ensure washing facilities after working hours and before breaks.

Take off contaminated or oil-soaked clothing immediately, wash with warm water and soap.

After splashing floor may be slippery, use care to avoid falling, contain spills immediately.

When using do not eat, drink or smoke.

Handling temperature: not available

7.2 Conditions for safe storage, including any incompatibilities

Store in dry, well ventilated place in original, tightly closed containers.

Keep away from direct heat, ignition sources and strong oxidizing agents.

Recommended storage temperature: max. 45°C

7.3 Specific end use(s)

Metallurgical lubricating grease.

8. Exposure controls / personal protection

Engineering control measures:

Not required.

8.1 Control parameters: -

8.2 Exposure controls

Personal protection:

Respiratory protection: Breathing apparatus not required.

Hand protection: Oil resistant gloves (EN 374, Breakthrough time 480 min)

(e.g. nitrile rubber – minimal thickness 0.33 mm).

Note: Manufacturer's directions for use and the conditions of

application should be observed.

Eye protection: Protective goggles not required. Skin protection: Protective clothing (oil resistant).

Other special: no data

Environmental exposure controls:

Do not discharge into drains/surface waters/groundwater.

MOL-LUB Ltd.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: MOL Aluroll 2EPG metallurgical lubricating grease

Version: 2 Latest revision: 20. 03. 2012 Date of issue: 20. 06. 2007 Page: 7/(11)

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:

Physical state: consistent

Colour: black, homogenous Odour: characteristic

Change in physical state:

Dropping point (ISO 2176): typ. 230°C not available

Others:

Flash point (COC) (EN ISO 2592): > 200°C (base oil)
Ignition point (EN ISO 2592): not available
Autoignition temperature: not available
Explosive properties: not explosive
Oxidizing properties: not oxidize
Vapour pressure at 20°C: negligible
Density at 20°C: not available

Solubility in water: practically insoluble in water

n-Octanol/water partition coefficient: not available Penetration after working – 60 c, at 25°C typ. 280

(0,1 mm) (ISO 2137):

pH: not applicable

9.2 Other information

no data available

10. Stability and reactivity

10.1 Reactivity: Dangerous reactivity not known.

10.2 Chemical stability: No decomposition if stored and handled properly.

10.3 Possibility of hazardous

reactions: Not known.

10.4 Conditions to avoid: Direct heat or ignition sources, open flames.

10.5 Incompatible materials: Strong oxidizing agents.

10.6 Hazardous decomposition No dangerous decomposition products are formed under normal

products: conditions. Hazardous combustion products: See Section 5.

MOL-LUB Ltd.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: MOL Aluroll 2EPG metallurgical lubricating grease

Version: 2 Latest revision: 20. 03. 2012 Date of issue: 20. 06. 2007 Page: 8/(11)

11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

Oral: LD_{50} (rat) > 2000 mg/kg (based on components) Dermal: LD_{50} (rabbit) > 2000 mg/kg (based on components)

Acute toxicity: irritation

Skin: not irritant (based on components)
Eye: not irritant (based on components)

Note: Prolonged and/or repeated contact may cause irritation on skin or in eyes

depending on individual sensitivity.

Respiratory or skin sensitisation: not sensitising (based on components)

Chronic toxicity: not known

Other information, specific effects:

The product does not contain PCBs, PCTs, and other chlorine compounds, and heavy metals, barium compounds.

Note L: The classification as a carcinogen need not apply according to 1272/2008/EC, because it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.

Carcinogen effect: not known, resp. not carcinogen (based on

components)

Mutagen effect: not known, resp. not mutagen (based on components)
Reproduction-damaging not known, resp. no reproduction-damaging effect

effect: (based on components)

Repeated dose toxicity: not known

12. Ecological information

12.1 Toxicity No data available.

Aquatic organisms: Soil organisms:

Plants:

12.2 Persistence and degradability

Biodegradability: No data available.

MOL-LUB Ltd.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: MOL Aluroll 2EPG metallurgical lubricating grease

Version: 2 Latest revision: 20. 03. 2012 Date of issue: 20. 06. 2007 Page: 9/(11)

12.3 Bioaccumulative potential No data available.

12.4 Mobility

Mobility in soil: Soil is not mobile.

Mobility in water: Floats on water. Does not form continuous layer.

12.5 Results of PBT and vPvB Not required.

assessment

12.6 Other adverse effects

Heavy metal content: None. PCT, PCB and other chlorinated None.

hydrocarbons:

Environmental effects: Large spillages may be hazardous to the environment.

Water hazard class (German): -

13. Disposal considerations

13.1 Waste treatment methods

Product disposal:

Wastes of the product or used oil should be treated as hazardous waste.

EWC cod: 12 01 12* Spent waxes and fats.

Disposal must be in compliance with national and local regulations.

Packaging disposal:

Containers with product residue should also be treated as hazardous waste according to national and local disposal regulations.

EWC cod: 15 01 10*

Packaging containing residues of or contaminated by dangerous substances.

Disposal must be in compliance with national and local regulations.

Recommended waste treatment method: incineration

Wastewater:

Quality of wastewater emitted to natural water must comply with national and local regulations.

Care should be taken in any case to ensure compliance with EC, national and local regulations. It is the responsibility of the user to know all relevant national and local regulations.

MOL-LUB Ltd.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: MOL Aluroll 2EPG metallurgical lubricating grease

Version: 2 Latest revision: 20. 03. 2012 Date of issue: 20. 06. 2007 Page: 10/(11)

14. Transport information

Land transport:

Road/ Railway ADR/RID: Not classified.

Waterways:

Inland waterways/ Sea transport ADN/IMDG: Not classified.

Air transport: ICAO / IATA: Not classified.

15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the mixture. This safety data sheet has been prepared according to Regulation (EC) No 1907/2006 and to Regulation (EC) 1272/2008.

15.2 Chemical safety assessment. not available

16. Other information

The information given in this data sheet is based on our best knowledge at the time of publication. The information is related only to this product and is intended to assist its safe transport, handling and use. The given physical and chemical parameters describe the product only for the purpose of safety requirements and therefore should not be construed as guaranteeing any specific property of the product or as being part of a product specification or any contract.

The manufacturer or supplier shall not take responsibility for any damages from the use other than recommended or other misuse of the product. It is the responsibility of the user to keep regulatory precautions and observe recommendations for safe use of the product.

Source of data presented in this material safety data sheet:

Test results of this product

Material safety data sheets of product's components

Hungarian and EU lists of dangerous substances

Relevant Hungarian regulation and EU directives

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 (CLP)

-

MOL-LUB Ltd.

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC

Trade name: MOL Aluroll 2EPG metallurgical lubricating grease

Version: 2 Latest revision: 20. 03. 2012 Date of issue: 20. 06. 2007 Page: 11/(11)

The full text of each relevant Hazard classes and cat., R- and H- phrase in Section 3.:

•	•
R 22	Harmful if swallowed.
R 35	Causes severe burns.
R 36/38	Irritating to eyes and skin.
R 38	Irritating to skin.
R 41	Risk of serious damage to eyes.
R 51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the
	aquatic environment.
R 50	Very toxic to aquatic organisms.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
Acute Tox. 4	Acute toxicity Category 4
Asp.Tox.1	Aspiration hazard Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Aquatic Acute 1	Hazardous to the aquatic environment, Acute Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, Chronic Category 2

Revision Indicators:

Section	Subject of change	Date	Version
3	Composition/information on ingredients	20.03.2012	2
1-16	Revision modification according to 453/2010/EC and		
	1272/2008/EC		