



SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC **MOL-LUB Ltd.**

Trade name: **MOL Dynamic MK 9 15W-40 multigrade diesel engine oil**

Version: 6 Latest revision: 14. 09. 2015 Date of issue: 20. 06. 2007 Page: 1/(14)

Section 1 Identification of the mixture and of the company/undertaking

1.1 Product identifier:

MOL Dynamic MK 9 15W-40 multigrade diesel engine oil

1.2 Relevant identified uses of the mixture and uses advised against

Relevant identified uses: multigrade diesel engine oil

Uses advised against: no data

1.3 Details of the supplier of the safety data sheet:

MOL-LUB Lubricant Production Trade and Service Limited Liability Company

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 34 526 330 / +36 34 526 391

E-mail: kenoanyag@mol.hu

Request SDS of:

MOL-LUB Lubricant Production Trade and Service Limited Liability Company

Customer Service Center

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 80 201 296 / +36 34 348 010

Responsible for SDS:

MOL-LUB Ltd. Csaba Horváth, head of SD, HSE & Business Support

Phone: +36 34 526 343; Mobile: +36 20 474 2644

e-mail: csahorvath@mol.hu

1.4 Emergency telephone number

Emergency telephone (07-15²⁰ h): +36 34 526 210 (CET) on workdays

Health Toxicological Information Service (ETTSZ 1096 Budapest, Nagyvárad tér 2.)

Tel.: +36 1 476 6464, or +36 80 201 199

National Health Toxicological Information Service:



SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC **MOL-LUB Ltd.**

Trade name: **MOL Dynamic MK 9 15W-40 multigrade diesel engine oil**

Version: 6 Latest revision: 14. 09. 2015 Date of issue: 20. 06. 2007 Page: 2/(14)

Section 2 Hazards identification

2.1 Classification of the mixture

Classification of the mixture according to regulation 1272/2008/EC

Hazard Class and Category: Hazard statement:
Eye Irrit. 2 H319 Causes serious eye irritation.

2.2 Label elements ((EC) No 1272/2008)

Product identification: Trade name: **MOL Dynamic MK 9 15W-40 multigrade diesel engine oil**

Hazardous components: -

GHS Pictogram:



Signal word: **Warning**

Hazard statement:
H319 Causes serious eye irritation.

Supplemental hazard information: -

Precautionary statements – General: -

Precautionary statements – Prevention:

P273 Avoid release to the environment.

P280 Wear eye/face protection.

Precautionary statements – Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

Precautionary statements – Storage: -



SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC **MOL-LUB Ltd.**

Trade name: **MOL Dynamic MK 9 15W-40 multigrade diesel engine oil**

Version: 6 Latest revision: 14. 09. 2015 Date of issue: 20. 06. 2007 Page: 3/(14)

Precautionary statements – Disposal:

P501 Dispose of contents/container in accordance with national regulation.

Other liabilities for labelling:

Tactile warning of danger: Not required.

Transport classification: see section 14.

2.3 Other hazards

The product does not contain any PBT or vPvB substance according to annex XIII of regulation (EC) 1907/2006.

Section 3 Composition/information on ingredients

3.2 Mixtures

Chemical description: Mixture of refined mineral base oils containing additives.

Component(s) / Hazardous component(s):

Name	EU number	CAS number	Hazard classes and cat.	Hazard statements	Conc. % (m/m)
Lubricating oils (petroleum), C24-C50* REACH Registr. Nr.: 01-2119489969-06	309-877-7	101316-72-7	Asp.Tox.1 (Note L)	H304	max. 40
Lubricating oils (petroleum), C18-C40* REACH Registr. Nr.: 01-2119486987-11	305-594-8	94733-15-0	Asp.Tox.1 (Note L)	H304	max. 30
Base oil – unspecified, hydrotreated heavy paraffinic, C20-C50*	265-157-1	64742-54-7	- (Note L)	-	max. 30
Distillates (petroleum), solvent-dewaxed heavy paraffinic C20-C50	265-169-7	64742-65-0	- (Note L)	-	max. 30
Lubricating oils (petroleum), C>25* REACH Registr. Nr.: 01-2119486948-13	309-874-0	101316-69-2	- (Note L)	-	max. 20



SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC **MOL-LUB Ltd.**

Trade name: **MOL Dynamic MK 9 15W-40 multigrade diesel engine oil**

Version: 6 Latest revision: 14. 09. 2015 Date of issue: 20. 06. 2007 Page: 4/(14)

Name	EU number	CAS number	Hazard classes and cat.	Hazard statements	Conc. % (m/m)
Mineral oil raffinate*		confidential	- (Note L)	-	max. 10
Zinc alkyl dithiophosphate	272-028-3	68649-42-3	Skin Irrit. 2 Eye Dam. 1 Aquatic Chronic. 2	H315 H318 H411	max. 1.5
Phenol, 4-dodecyl-	203-202-9	104-43-8	Repr. 2 Skin Irrit. 2 Aquatic Acute 1 Aquatic Chronic 1	H361f H315 H400 H410	max. 0.13

*: with exposure limit

The full text of each relevant H- phrase and Hazard classes and cat. see in Section 16.

Section 4 First aid measures

4.1 Description of first aid measures

General information: Never give anything by mouth to an unconscious person, or never induce vomiting.

Inhalation: Remove the affected person to fresh air. If rapid recovery does not occur, obtain medical attention.

Skin contact: Remove contaminated clothing. Wash skin with large amounts of water, use soap. In case of persistent irritation, get medical attention.

Skin contact: Remove contaminated clothing. Wash skin with large amounts of water, use soap. In case of persistent irritation, get medical attention.

Eye contact: Flush eyes with plenty of water for 10-15 minutes. In case of persistent irritation, get medical attention.

Ingestion: If swallowed, give water. **Do not** induce vomiting. Get medical attention.

Protection of first-aid person: No individual specifications.



SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC **MOL-LUB Ltd.**

Trade name: **MOL Dynamic MK 9 15W-40 multigrade diesel engine oil**

Version: 6 Latest revision: 14. 09. 2015 Date of issue: 20. 06. 2007 Page: 5/(14)

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment need

Not required.

Section 5 Fire-fighting measures

Fire hazards:

Combustible

5.1 Extinguishing media

Suitable extinguishing media:

Foam, carbon dioxide, dry chemical powder.

Unsuitable extinguishing media:

Water jet.

5.2 Special hazards arising from the mixture

Hazardous combustion products:

On burning, carbon dioxide, carbon monoxide, sulphur oxides, phosphor oxides, various hydrocarbons and soot can be formed.

5.3 Advice for fire-fighters

Special protective equipment:

According to the existing fire-fighting regulations. Respiratory protection.

Further information:

Collect contaminated fire fighting water separately. It must not enter the sewage system. Contaminated extinguishing water must be disposed of in accordance with official regulations.

Section 6 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: see Section 8.



SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC **MOL-LUB Ltd.**

Trade name: **MOL Dynamic MK 9 15W-40 multigrade diesel engine oil**

Version: 6 Latest revision: 14. 09. 2015 Date of issue: 20. 06. 2007 Page: 6/(14)

6.2 Environmental precautions:

Confine spills to prevent material from entering sewers, watercourses, drains and into soil Notify relevant authority.

6.3 Methods and material for containment and cleaning up

On soil: All kind of ignition sources should be remove. Recover free liquid by pumping. Contain the rest or small quantities with sand, earth or other suitable absorbents. Dispose of according to local regulations.

On water: Confine the spillage. Remove from surface by skimming or suitable absorbents. Notify local authorities according to regulations.

6.4 Reference to other sections

Personal precautions: see section 8.

Waste treatment methods: see section 13.

Section 7 Handling and storage

7.1 Precautions for safe handling

Keep general measures applied for normal operations with lubricants and flammable liquids.

Keep away from radiant heat and open flame.

Avoid contact with skin and eyes. Avoid prolonged breathing of oil vapours or mists.

Ensure washing facilities after working hours and before breaks. Take off contaminated or oil-soaked clothing, wash with warm water and soap.

When using do not eat, drink or smoke. Avoid splashing the product.

Handling temperature: not known

7.2 Conditions for safe storage, including any incompatibilities

Storage facilities must comply with regulations for storing of flammable liquids.

Store in dry, well ventilated place in original, closed containers.

Keep away from radiant heat, open flame and strong oxidizing agents.

Storage temperature: max. 40°C

7.3 Specific end use(s)

Multigrade diesel engine oil.



SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC **MOL-LUB Ltd.**

Trade name: **MOL Dynamic MK 9 15W-40 multigrade diesel engine oil**

Version: 6 Latest revision: 14. 09. 2015 Date of issue: 20. 06. 2007 Page: 7/(14)

Section 8 Exposure controls / personal protection

Engineering control measures:
Not required.

8.1 Control parameters:

Mineral oil mist: TWA: **5 mg/m³**; STEL: 10 mg/m³, for oil mist, vapour excluded (ACGIH).

Method of testing, recommended: NIOSH 5026

8.2 Exposure controls

Personal protection:

Respiratory protection: Breathing apparatus not required.

Hand protection: Oil resistant gloves (EN 374, Breakthrough time 480 min) (e.g. nitrile rubber – minimal thickness 0.33 mm).

Note: Manufacturer's directions for use and the conditions of application should be observed.

Eye protection: Tightly fitting safety goggles.

Skin protection: Protective clothing (oil resistant).

Other special: no data

Environmental exposure controls:

Do not discharge into drains/surface waters/groundwater.

Section 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:

Physical state:	liquid
Colour:	brown, clear
Odour:	characteristic

Change in physical state:

Pour point (ISO 3016):	typ. -33°C
Boiling point (DIN 51356):	not available

Others:

Flash point (COC) (EN ISO 2592):	typ. 230°C
----------------------------------	------------



SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC **MOL-LUB Ltd.**

Trade name: **MOL Dynamic MK 9 15W-40 multigrade diesel engine oil**

Version: 6 Latest revision: 14. 09. 2015 Date of issue: 20. 06. 2007 Page: 8/(14)

Ignition point (EN ISO 2592):	not available
Autoignition temperature:	not available
Explosive properties:	not explosive
Oxidizing properties:	not oxidize
Vapour pressure at 20°C:	negligible
Density at 15°C (EN ISO 12185):	0.870 – 0.890 g/cm ³
Solubility in water:	practically insoluble in water
Solubility in other solvents:	gasoline, kerosene, toluene, etc.
n-Octanol/water partition coefficient:	not available
Vapour density:	not available
Heating value:	inf. 38 000 kJ/kg
Kinematic viscosity at 40°C (EN ISO 3104):	typ. 115.5 mm ² /s
Kinematic viscosity at 100°C (EN ISO 3104):	typ. 15.4 mm ² /s
pH:	not applicable

9.2 Other information
no data available

Section 10 Stability and reactivity

10.1 Reactivity:	Dangerous reactivity not known.
10.2 Chemical stability:	No decomposition if stored and handled properly.
10.3 Possibility of hazardous reactions:	Not known.
10.4 Conditions to avoid:	Direct heat or ignition sources.
10.5 Incompatible materials:	Strong oxidizing agents.
10.6 Hazardous decomposition products:	No dangerous decomposition products are formed under normal conditions. Hazardous combustion products: See Section 5.

Section 11 Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

Oral:	LD ₅₀ (rat)	> 2000	mg/kg	(based on components)
Dermal:	LD ₅₀ (rabbit)	> 2000	mg/kg	(based on components)



SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC **MOL-LUB Ltd.**

Trade name: **MOL Dynamic MK 9 15W-40 multigrade diesel engine oil**

Version: 6 Latest revision: 14. 09. 2015 Date of issue: 20. 06. 2007 Page: 9/(14)

Acute toxicity: irritation

Skin: not irritant (based on components)

Note: Prolonged and/or repeated contact may cause irritation on skin depending on individual sensitivity.

Eye: irritant (based on components), causes serious eye irritation

Respiratory or skin sensitisation: not sensitising (based on components)

Other information, specific effects:

The product does not contain PCBs, PCTs, and other chlorine compounds, and heavy metals, barium compounds.

Note L: The classification as a carcinogen need not apply according to 1272/2008/EC, because it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.

Germ cell mutagenicity: not known, resp. not mutagen (based on components)

Carcinogenicity: not known, resp. not carcinogen (based on components)

Reproductive toxicity: not known, resp. no reproduction-damaging effect (based on components)

STOT-single exposure: not known

STOT-repeated exposure: not known

Aspiration hazard: not known

Section 12 Ecological information

12.1 Toxicity No data for the product.

Aquatic organisms:

Soil organisms:

Plants:

12.2 Persistence and degradability No data available.

Biodegradability: No data available.

12.3 Bioaccumulative potential No data available.

12.4 Mobility

Mobility in soil Absorbs in soil.

Mobility in water: Floats on water.



SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC **MOL-LUB Ltd.**

Trade name: **MOL Dynamic MK 9 15W-40 multigrade diesel engine oil**

Version: 6 Latest revision: 14. 09. 2015 Date of issue: 20. 06. 2007 Page: 10/(14)

12.5	Results of PBT and vPvB assessment	Does not contain PBT and vPvB substances.
12.6	Other adverse effects	
	Heavy metal content:	None.
	PCT, PCB and other chlorinated hydrocarbons:	None.
	Environmental effects:	Spills may form a film on water surfaces causing impaired oxygen transfer.
	Water hazard class (German):	WGK 1 (Classification by VwVwS)

Section 13 Disposal considerations

13.1 Waste treatment methods

Product disposal:

Wastes of the product or used oil should be treated as hazardous waste.

Waste Identification Code: 13 02 05*

Mineral-based non-chlorinated engine, gear and lubricating oils.

Recommended waste treatment method: incineration

Packaging disposal:

Containers with product residue should also be treated as hazardous waste according to national and local disposal regulations.

Waste Identification Code: 15 01 10*

Packaging containing residues of or contaminated by dangerous substances.

Disposal must be in compliance with national and local regulations.

Wastewater:

Quality of wastewater emitted to natural water must comply with national and local regulations.

Care should be taken in any case to ensure compliance with EC, national and local regulations. It is the responsibility of the user to know all relevant national and local regulations.



SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC **MOL-LUB Ltd.**

Trade name: **MOL Dynamic MK 9 15W-40 multigrade diesel engine oil**

Version: 6 Latest revision: 14. 09. 2015 Date of issue: 20. 06. 2007 Page: 12/(14)

Source of data presented in this material safety data sheet:

- Test results of this product
- Material safety data sheets of product's components
- Hungarian and EU lists of dangerous substances
- Relevant Hungarian regulation and EU directives

Classification for mixtures and used evaluation method according to regulation 1272/2008/EC (CLP)

Eye Irrit. 2 H319 calculation method

The full text of each relevant H- phrase and Hazard classes and cat. in Section 3.:

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H361f	Suspected of damaging fertility..
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Asp.Tox.1	Aspiration hazard Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Repr. 2	Reproductive toxicity Category 2
Aquatic Acute 1	Hazardous to the aquatic environment, Acute Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, Chronic Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, Chronic Category 2

Legend:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate



SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC **MOL-LUB Ltd.**

Trade name: **MOL Dynamic MK 9 15W-40 multigrade diesel engine oil**

Version: 6 Latest revision: 14. 09. 2015 Date of issue: 20. 06. 2007 Page: 13/(14)

BCF	Bioconcentration Factor
BOD	Biological Oxygen Demand
Bw	Body Weight
C&L	Classification and Labeling
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic or toxic to Reproduction
COD	Chemical Oxygen Demand
CSA	Chemical Safety Assessment
CSR	Chemical Safety Report
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
ECHA	European Chemicals Agency
Ec _x	Effective Concentration x%
Ed _x	Effective Dose x%
ELINCS	European List of Notified Chemical Substances
ErC ₅₀	EC ₅₀ in terms of reduction of growth rate;
ES	Exposure Scenario
ESIS	European Chemical Substances Information System
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC _x	Lethal Concentration x%
LD _x	Lethal Dose x%
LOAEC	Lowest Observed Adverse Effect Concentration
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
NOEC	No observed effect concentration
NOEL	No observed effect level
NLP	No-Longer Polymer
NOAEL	No Observed Adverse Effect Level
OECD	Organisation for Economic Cooperation and Development
PBT	Persistent Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SVHC	Substance of Very High Concern
UVCB	substance of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bio-accumulative



SAFETY DATA SHEET

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC **MOL-LUB Ltd.**

Trade name: **MOL Dynamic MK 9 15W-40 multigrade diesel engine oil**

Version: 6 Latest revision: 14. 09. 2015 Date of issue: 20. 06. 2007 Page: 14/(14)

Revision Indicators:

Section	Subject of change	Date	Version
3 1-16	Composition / information on ingredients Revision modification according to REACH (1907/2006/EC)	26.02.2008	2
1 3	Product name Composition / information on ingredients Other corrections	08.02.2010	3
3 1-16	Composition/information on ingredients Revision modification according to 453/2010/EC	13.05.2011	4
2 3 9 11 1-16	Hazards identification Composition/information on ingredients Physical and chemical properties Toxicological information Revision modification according to 1272/2008/EC	27.05.2013	5
1 3 9 1-16	Details of the supplier of the safety data sheet, Responsible for SDS Composition/information on ingredients Physical and chemical properties Other corrections, revision modification according to 2015/830 /EU	14.09.2015	6