

MOL Dynamic Garden 4T 10W-30

garden equipment motor oil



MOL Dynamic Garden 4T 10W-30 is a special engine oil produced from synthetic base oils using a complex additive system, that ensures the highest performance level and the good flow characteristics, for use in small gardening machines. It meets and even outperforms the engine oil specifications issued by the leading manufacturers of small gardening machines, including MTD, Briggs & Stratton, Honda, and Tecumseh.

Application



Four-stroke engines of small garden equipment and power generators
Snow blower engines

Features and benefits

Excellent cold flow properties	Easy start-up even in cold weather
High performance level	Stable load-carrying lubricating film and high-level wear protection even under heavy loads
Exceptional thermal and oxidation stability	Resists ageing processes in the long term and harmful deposits are not formed
Outstanding shear stability	Sustains lubricity during long oil drain intervals

Specifications and approvals

Viscosity grade: SAE 10W-30
ACEA A3/B4
API SL/CF

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,867
Kinematic viscosity at 40°C [mm ² /s]	76,9
Kinematic viscosity at 100 °C [mm ² /s]	11,6
Viscosity index	144
Pour point [°C]	-36
Flash point (Cleveland) [°C]	230
Base number (BN) [mg KOH/g]	8,0

The characteristics in table are typical values of the product and do not constitute a specification.

MOL Dynamic Garden 4T 10W-30

garden equipment motor oil



Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C